

## BACKGROUND OF THE INVENTION

### FIELD OF THE INVENTION

The present invention is generally related to a color printing apparatus, or a color printing system, and more specifically, is directed to a print data control.

### DESCRIPTION OF THE RELATED ART

There are a color printing apparatus and a color printing system, capable of performing a color printing operation.

That is, for instance, an upper-grade apparatus such as a personal computer rasterizes print data constructed of characters/figures/images as multi-bits bitmap data indicated by color values of the respective primary colors, i.e., R(red), G(green), and B(blue) colors. Then, the rasterized bitmap data is transferred to a color printer control apparatus, while the bitmap data of RGB colors is directly sent or is converted into bitmap data of CMYK (cyan, magenta, yellow, black) colors corresponding to the primary colors printed by a color printer. In the color printer control apparatus, the received multi-bits bitmap data is converted into the color values of the primary colors CMYK printed by the color printer

5 operation is carried out. In particular, JP-A-5-83540  
discloses the following techniques. That is, the black  
character/black line image portion is extracted from  
the print data in which the color image data are mixed  
with the black/white data such as characters and lines.

However, the above-described printing  
20 technique does not consider lowering of the printing  
performance in such a case that since the print data is  
sent as the con-tone/multi-bits bitmap data from the  
upper-grade apparatus to the color printing apparatus,  
when the information amount of the print data is large,  
25 the data sending time is prolonged. Also, in the  
upper-grade apparatus, the above-explained printing  
technique owns such a problem that the rasterizing  
process time used to produce the print data is

5 thus, printing performance thereof would be lowered.

10 contained in a portion of a document, and/or color  
images are contained only in several pages among a  
plurality of document pages. However, the above-  
described printing technique never considers such  
various use modes. Since all of these documents are  
15 print-processed as the color printing data, this  
printing technique requires such lengthy printing time.

Also, in the above-described printing technique, the black character/black line image is extracted by the line/image extracting circuit from the print data in which the color image such as natural images is synthesized with the single-bit black/white image data such as characters and line images. However, the black characters of the image area could not be extracted. There has also been another related application, U.S. Patent Application Serial No. 09/095,889 filed June 11, 1998 and entitled "Information Printing System" by E. Yoshino, et al.

# SUMMARY OF THE INVENTION

The present invention is featured by that color print data is rasterized as con-tone/multi-bits bitmap data and also bi-tone/single-bit bitmap data, which are used as print data. These con-tone/multi-bits bitmap data and bi-tone/single-bit bitmap data are separately stored into a page memory, and then are converted into printing primary colors during print operation. The converted printing primary colors are printed out in the unit of the primary color, and furthermore, are logically calculated every bit so as to synthesize the calculated bitmap data with each other.

As one concrete example, while multi-bits bitmap data of RGB (red, green, blue) are converted into multi-bits bitmap data of CMYK (cyan, magenta, yellow, black) corresponding to the printing primary colors, the single-bit bitmap data of K color is OR-gated with the above-explained converted multi-bits bitmap data of K color every bit, and then the OR-gated bitmap data of K color is outputted during the printing operation of K color. When the printing operation of CMY colors is carried out, the single-bit bitmap data of K color is inverted every bit in such a manner that the multi-bits bitmap data of CMY colors are masked by the single-bit bitmap data of K color. Then, the inverted single-bit bitmap data of K color is AND-gated by the multi-bits bitmap data of CMY colors to output

Furthermore, when con-tone/multi-bits print data is stored into a page memory, bi-tone/single-bit bitmap data stored at the bit position corresponding thereto is set to non-print data.

Also, lowering of the above-explained printing performance can be solved as follows:

When the printing operations is carried out,

When the printing operations is carried out,

5 data to be printed is outputted to the color printing  
unit. As one concrete example, such a judgement is  
made as to whether or not the multi-bits bitmap data of  
RGB and the bi-tone/single-bit bitmap data of the page  
memory are present. In such a case that the print data  
0 of the bi-tone/single-bit is effective, only the print  
data of ~~K color~~ among the printing primary colors of  
~~CMYK~~ is ~~printed~~ out.

20 When the printing operation is carried out, the con-  
tone/multi-bits bitmap data is multiplied by "n", and  
then the n-multiplied con-tone/multi-bits bitmap data  
is logically synthesized with the bi-tone/single-bit  
bitmap data to output the synthesized bitmap data.

25           With employment of the above-explained means,  
the information amount of the print data can be reduced,  
and the useless printing operation is not carried out,  
so that the printing performance is not lowered.

## BRIEF DESCRIPTION OF THE DRAWINGS

A more better understanding of the present invention is made by reading a detailed description in conjunction with the accompanying drawings, in which:

5           Fig. 1 schematically shows a structural diagram of a color printing apparatus according to an embodiment of the present invention;

          Fig. 2 is an explanatory diagram for explaining a forming operation and a synthesizing  
10 operation of bitmap data according to the present invention;

          Fig. 3 is an explanatory diagram for describing a sending operation of only rasterized single-bit bitmap data;

15           Fig. 4 is an explanatory diagram for describing a sending operation of only rasterized multi-bits bitmap data;

          Fig. 5 is an explanatory diagram for explaining a printing operation of single-bit bitmap  
20 data, the resolution of which is increased; and

          Fig. 6 schematically represents a structural diagram of a color printing apparatus according to another embodiment of the present invention.

## DETAILED DESCRIPTION OF THE EMBODIMENT

25           Referring now to drawings, an embodiment of the present invention will be described in detail. It

09048643 "052300

should be noted that in this embodiment, the present invention is described in the form of a color printer control apparatus 101. Alternatively, such an arrangement constituted by combining the color printer control apparatus 101 and a color printer apparatus 102 may be explained as a color printing apparatus of the present invention.

Fig. 1 schematically indicates an example of an apparatus which constitutes a color printing system according to an embodiment of the present invention. This color printing system is arranged by an upper-grade apparatus 100, a color printer control apparatus 101, and a color printer apparatus 102. In this drawing, there is shown a major arrangement as to the color printer control apparatus 101. The color printer apparatus 102 is, for instance, a color laser printer.

In the upper-grade apparatus 100, an application program 103 transfers print data such as character/figure (drawing)/image data to a printer driver 104 so as to instruct the printing operation. When the printer driver 104 receives the print instruction issued from the application program 103, this printer driver 104 rasterizes the transferred print data so as to form bitmap data. At this time, in the case that the color of the character/figure/image data to be rasterized is black, the printer driver 104 forms single-bit bitmap data 105, whereas in the case that the color of the character/figure/image data is



5 the case that color values of R(red), G(green), and  
B(blue) are defined as R=0, G=0, and B=0, a black color  
is represented.

10 colors of R, G, B, and color values of the respective  
colors are selected to be "0" to "255". For instance,  
when the print data corresponds to bitmap data 200 to  
202 shown in Fig. 2, it is so assumed that the printer  
driver 104 rasterizes this print data to produce both  
15 single-bit bitmap data 205 and multi-bits bitmap data  
208. When a completion of rasterizing operation for  
print data in unit of one page is notified from the  
application program 103, the printer driver 104 sends  
out the formed bitmap data to the color printer control  
20 apparatus 101. In such a case that the printer driver  
104 sends out the single-bit bitmap data 105, this  
printer driver 104 adds thereto a single-bit data  
command 119 capable of discriminating such a fact that  
this sent print data corresponds to the single-bit  
25 bitmap data, whereas in such a case that the printer  
driver 104 sends out the multi-bits bitmap data 105,  
this printer driver 104 adds thereto a multi-bits data  
command 120 capable of discriminating such a fact that

this sent print data corresponds to the multi-bits bitmap data. Then, the printer driver 104 supplies the resulting print data with the data command to the color printer control apparatus 101.

Alternatively, as to such bitmap data which has not yet been rasterized, a rasterize flag may be provided in order to recognize as to whether or not rasterized print data is present. As a result, it is readily possible not to send out such bitmap data without the rasterized print data to the color printer control apparatus 101. For instance, when the printer driver 104 receives the print operation instructed from the application program 103, while both the single-bit rasterize flag 122 and the multi-bits rasterize flag 123 are initialized as values capable of discriminating "no data", in the case that the print data whose character/figure/image data color is black is rasterized as the single-bit bitmap data, the printer driver 104 sets a value capable of discriminating "data is present" to the single-bit rasterize flag 122. When the print data whose character/figure/image data color is any color other than black color is rasterized, the printer driver 104 sets a value capable of discriminating "data is present" to the multi-bits rasterize flag 123.

When bitmap data is sent out to the color printer control apparatus 101, the printer driver 104 may transfer such a bitmap data which indicates "data

is present" by using either the single-bit rasterize  
flag 122 or the multi-bits rasterize flag 123 to the  
color printer control apparatus 101, whereas the  
printer driver 104 may not transfer such a bitmap data  
5 which represents "no data" to the color printer control  
apparatus 101. Furthermore, when the bitmap data in  
the unit of one page is sent out to the color printer  
control apparatus 101, the printer driver 104 transfers  
a page end command 124 to the color printer control  
10 apparatus 101. In the color printer control apparatus  
101, the print data received from the upper-grade  
apparatus 100 is stored into a reception buffer 107.  
An MPU (microprocessor unit) 108 reads out a command  
from the reception buffer 107 so as to discriminate  
15 that the bitmap data corresponds to the single-bit  
bitmap data, or the multi-bits bitmap data, and then  
stores the discriminated bitmap data into a page memory  
109. Upon detection of the page end command 124, the  
MPU 108 initiates an output control unit 110 so as to  
20 convert the bitmap data stored in the page memory 109  
into video signals made of the respective primary  
colors CMYK, and then, supplies these converted video  
signals to the color printer apparatus 102. The color  
printer apparatus 102 prints in response to the video  
25 signal sent from the color printer control apparatus  
101.

The output control unit 110 owns a function  
capable of synthesizing the single-bit bitmap data 111

20           In a so-called "intermediate transfer type  
color laser printer", since toners having primary  
colors CMYK are sequentially adhered to an intermediate  
transfer drum so as to print out a color image, the  
bitmap data stored in the page memory 109 are read out  
25 4 times in correspondence with the respective primary  
color outputs of CMYK. The MPU 108 controls the  
primary color selecting circuit 117 of the output  
control unit 110 to sequentially select the primary

color data to be outputted, so that the video signal having the relevant color is outputted.

It is now assumed that the synthesizing operation between the single-bit bitmap data 111 and the multi-bits bitmap data 112 is carried out as shown in Fig. 2. That is, for example, assuming now that both the single-bit bitmap data 111 and the multi-bits bitmap data 112, which are stored in the page memory 109, are equal to both single-bit bitmap data 205 and multi-bits bitmap data 208 indicated in Fig. 2, the output of the AND gate circuit 114 becomes multi-bits bitmap data 209 shown in Fig. 2, and then, a printout result 210 is obtained by both bitmap data of K(black) color synthesized with the above-described multi-bits bitmap data 209 and bitmap data of CMY (cyan, magenta, and yellow) colors equal to the output of the color converting circuit 115 by the OR gate circuit 116.

Also, depending upon a page to be printed out, there is such a case that a page is printed out by using only single-bit bitmap data. Further, there is another case that a page is printed out by employing only multi-bits bitmap data. While the MPU 108 controls the print mode control circuit 121, this print mode control circuit 121 may synthesize the single-bit bitmap data with the multi-bits bitmap data to output print data made of the synthesized bitmap data, may output print data made of only the single-bit bitmap data, or may output print data made of only the multi-

bits bitmap data. In other words, when the print mode control circuit 121 is set to such a print mode that the print data made of only the single-bit bitmap data is outputted, the multi-bits bitmap data is not read out, but outputs such print data in such a way that the input of the AND gate circuit 114 becomes white data (R=255, G=255, B=255). Also, when the print mode control circuit 121 is set to such a print mode that the print data made of only the multi-bits bitmap data is outputted, the print mode control circuit 121 does not read the single-bit bitmap data, but outputs such print data that the inputs of the NOT gate circuit 113 and the OR gate circuit 116 become white data "0." As previously described, while the print data of the character/figure/image data whose color is black is rasterized as the single-bit bitmap data and also the color data other than black color data are rasterized as the multi-bits bitmap data, the single-bit bitmap data is synthesized with the multi-bits bitmap data during the printing operation to print out. As a result, it is possible to shorten the process time required to rasterize the print data of the character/figure/image data whose color is black, and therefore, the printing performance can be improved. Also, even when color document data made of plural pages is printed in the color print mode, if there are such pages made of the print data of the character/figure/image data whose color is black, then



5  
10  
15  
20  
25



5  
10

15  
20

25

not coded, but only the rasterized data portion is merely coded. As a result, the process operation required to code the rasterized bitmap data portion can be shortened, and therefore, the print performance can be improved. In particular, there are many possibilities in a color document that print data of character/figure/image data whose color is black is printed on an area (for example, bank) different from another area where print data whose color is any color other than black color is printed. As a result, only the rasterized data portion may be sent out, and/or may be encoded. Thus, it is expectable that both the data transfer time and the encoding process time may be reduced to improve the printing performance in the color document.

Referring now to Fig. 5 and Fig. 6, a description will be made of a color printing system capable of improving a printing quality in accordance with the below-mentioned color printing operation. That is, resolution of single-bit bitmap data is increased and the resolution-increased bitmap data is rasterized, whereas multi-bits bitmap data is rasterized with 1/n resolution of that of the single-bit bitmap data. When the printing operation is carried out, this resolution of the multi-bits bitmap data is converted into such resolution equal to the above-described resolution of the single-bit bitmap data, and then the single-bit bitmap data is

In the upper-grade apparatus 100, upon receipt of a print instruction issued from the application program 103, the printer driver 104 rasterizes the print data of the character/figure/image data whose color is black as single-bit bitmap data 500 of 600 dpi, whereas the print data whose color is any color other than black color is rasterized as multi-bits bitmap data 501 of 300 dpi. In this case, when a m/m unit and a point (namely, 1 point = 1/72 inches) are quantized as dot numbers of resolution of 600 dpi and 300 dpi, the dot number of 600 dpi is not always equal to two times of the dot number of 300 dpi. The conversion from m/m unit and point into dot numbers of dpi corresponds to such a conversion between different unit systems. Thus, the dot number converted into dpi may contain such an error that small numbers less than a decimal point is rounded with respect to numeral

values indicated by m/m unit and point. As a consequence, the following case does not always occur. That is, the dot number converted into resolution of 600 dpi owns an error smaller than that of the dot number converted into resolution of 300 dpi, and the dot number of 600 dpi converted from either m/m unit or point becomes two times larger than the dot number converted into 300 dpi. For example, when 10 points are rounded by cutting off numbers smaller than the decimal point, resolution of 600 dpi becomes 83 dots and resolution of 300 dpi becomes 41 dots. To solve this error aspect, the conversion from either m/m unit or point into 600 dpi may be carried out in such a manner that dot number of 300 dpi is calculated from either m/m unit or point, and then the calculated dot number is multiplied by two. As previously described, the color printing operation is carried out as follows. That is, both the single-bit bitmap data of 600 dpi and the multi-bits bitmap data of 300 dpi, which are rasterized in the upper-grade apparatus 100, are sent to the color printer control apparatus 101. In this color printer control apparatus 101, the multi-bits bitmap data is enlarged two times along both a main scanning direction (lateral direction) and a sub-scanning direction (longitudinal direction) so as to become such bitmap data having the same size as that of 600 dpi. When the multi-bits bitmap data of 300 dpi is enlarged, various methods may be performed. That is,

when the MPU 108 stores the multi-bits bitmap data of 300 dpi into the page memory, this multi-bits bitmap data may be enlarged two times along the lateral and longitudinal directions and then the enlarged bitmap data may be stored into the page memory. Alternatively, while an enlarging circuit 600 is added to the print mode control circuit 121, the multi-bits bitmap data read out from the page memory 109 may be enlarged two times along both the lateral and longitudinal directions, so that the input data to the AND gate circuit 114 may become multi-bits bitmap data of 600 dpi. If the input data to the AND gate circuit 114 becomes the multi-bits bitmap data of 600 dpi, as previously explained in connection with Fig. 1, then this multi-bits bitmap data of 600 dpi is synthesized with the single-bit bitmap data of 600 dpi, and thus, the video signal having resolution of 600 dpi may be sent to the color printer apparatus 102 so as to perform the color printing operation.

As previously explained, while the print data of the character/figure/image data whose color is black is rasterized as the single-bit bitmap data having the high resolution and also the print data whose color is any color other than black color is rasterized as the multi-bits bitmap data having the  $1/n$  resolution lower than that of the multi-bits bitmap data, the resolution of the multi-bits bitmap data is converted into that of the single-bit bitmap data to print out during the

printing operation. As a consequence, while the increasing of the information amount is suppressed, the print qualities of the black characters and the black lines can be improved.

5                   As previously explained, such a color printing system has been described as one embodiment of the present invention, in which the bitmap data is produced in the upper-grade apparatus 100, and then the produced bitmap data is supplied to the color printer  
10 control apparatus 100 so as to perform the color printing operation. The present invention may be similarly realized by way of the following printing method. That is, while print data constructed of characters/figures/images is sent out from the upper-  
15 grade apparatus 100 to the color printer control apparatus 101, the print data received by the color printer control apparatus 101 is rasterized to form the bitmap data.

009280" 57994950